

SPECIFICATIONS



Model

2 Seat - TC3/TC4

Weight

Final product weight will depend on configuration

22" Open Arm	51.5 lbs
22" Half Arm	66.5 lbs
22" Full Arm	81.5 lbs
30" Open Arm	64.3 lbs
30" Half Arm	79.3 lbs
30" Full Arm	94.3 lbs

Dimensions

Overall dimensions will vary depending on configuration

Seat	22"	30"
Seat Height	19.2"	19.2"
Seat Width	21.5"	29.5"
Arm Height	26.4"	26.4"
Overall Width	26.5"	34.5"
Overall Height	34.7"	34.7"
Overall Depth	26.2"	26.2"

*Intended for indoor use only

See page 2 for COM information.



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Available in California TB133 compliant upholstery. Bolt-down plate available.

Ballasting available:

25 lb plate for 22" Chair

35 lb plate for 30" Chair

*Ballasting must be communicated at time of order.

Assembly

No assembly required

Terra mixed seating expands the offering of traditional tandem seating with configuration combinations of 22" and 30" seat sizes.

Fabrication & Material

Frame: Welded steel frames

Cushions: Constructed of a 2.0 lb density seat foam wrapped in fabric with concealed staples.

Arm Caps: Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven

Arm Options: Open, Half Arm, & Full arm panels are MDF, foam & fabric

Glides: Non-removable Nylon Glides with secure hardware

Installation

Required for bolt-down

Warranty

10 year limited replacement

Maintenance

Frame: Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

Upholstery: Refer to upholstery manufacturer's cleaning instructions for specific fabric.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

COM YARDS

TC3 - Open Arm Chair

Total Yards	5.2
Seat Yards	2
Back Yards	3.2

TC3 - Half Arm Chair

Total Yards	7.75
Seat Yards	2
Back Yards	3.2
Arm Yards	2.55

TC3 - Full Arm Chair

Total Yards	10.18
Seat Yards	2
Back Yards	3.2
Arm Yards	4.98

TC4 - Open Arm Chair

Total Yards	5.2
Seat Yards	2
Back Yards	3.2

TC4 - Half Arm Chair

Total Yards	7.75
Seat Yards	2
Back Yards	3.2
Arm Yards	2.55

TC4 - Full Arm Chair

Total Yards	10.18
Seat Yards	2
Back Yards	3.2
Arm Yards	4.98