

# Vesta™

## Guest Arm Chair



<b>Model</b>	VA600
<b>Weight</b>	30 lbs / 13.6 kg

Dimensions	in	cm
Seat Height	18.2"	46.2
Seat Width	19"	48.3
Overall Height	33"	83.1
Overall Depth	26.6"	67.6
Width	24"	61
Arm Height	25.7"	65.3
Upholstery	yd	m
COM	1	0.9

\*View our upholstery selection on our website. Fabric Grades B - H and COM available.

### Finishes

See Design Guide for finish options.

### Options

- Upholstered Seat
- TB133 Upholstery Upgrade
- Bolt-Down Kit
- Factory Ballasting (50 lbs / 22.7 kg)

\*Ballastable up to 100 pounds (43.5 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

### Assembly

None required

\*Intended for indoor use only

### Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Ligature resistant design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

### Maintenance

**Seats** - For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

**Optional Upholstery** - Refer to Upholstery Manufacturers' cleaning instructions.

### Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)
- Tested to 750 lb (340.2 kg) static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards - Upholstered Chair

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

### Flammability Test Standards - Non-Upholstered Chair

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

