



| | |
|---------------|------------------|
| Model | VA610 |
| Weight | 24 lbs / 10.9 kg |

| Dimensions | in | cm |
|-------------------|-----------|-----------|
| Seat Height | 18.2" | 46.3 |
| Seat Width | 21" | 53.3 |
| Overall Height | 33" | 83.7 |
| Overall Depth | 26.5" | 67.4 |
| Width | 21" | 53.3 |
| Upholstery | yd | m |
| COM | 1 | 0.9 |

*View our upholstery selection on our website. Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- Upholstered Seat
- TB133 Upholstery Upgrade
- Bolt-Down Kit
- Factory Ballasting (50 lbs / 22.7 kg)

*Ballastable up to 100 pounds (45.4 kg) of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required

*Intended for indoor use only

Fabrication & Material

One-piece, rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Ligature resistant design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with a threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution, and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Seats - For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Optional Upholstery - Refer to Upholstery Manufacturer's cleaning instructions.

Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18") (113.4 kg from 45.7 cm)
- Tested to 750 lb (340.2 kg) static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards - Upholstered Chair

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Flammability Test Standards - Non-Upholstered Chair

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

